

# RX-50<sup>®</sup>

## Versatile Clinical Chemistry Analyzer

Enzymes | Substrates | Therapeutic Drugs | Electrolytes | Turbidimetry | Coagulation



# RX-50<sup>®</sup>

Versatile Clinical Chemistry Analyzer

## Features

- User friendly software
- End point method - Storage of abs of reagent blank in memory
- Editing of patient ID, name (12 characters), factor
- Print out of laboratory and doctor's name
- For kinetic test: On line graph and OD, graph editing facility, estimation of result
- Air purge between samples to avoid carry over / lamp saver mode
- 35 Direct test keys for test selection
- Utility mode for self diagnosis checking / 16 bit ADC
- Sample type: serum / plasma / CSF / urine / whole blood / hemolysate
- Calculator for lipid profile

## Methods of calculations

Absorbance / Fixed time / Kinetic /  
End point / Differential /  
Multipoint upto 10 standards

## Optical system

Principle: Absorption spectrophotometry  
Measurements: From -0.1 to 3.0A for  
340nm, -0.1 to 3.5A for WL  
range 405 to 670nm  
Filters: 340 - 630nm  
2 extra free positions  
Bandwidth: 8nm (±2nm)  
Reading Error: ±2% at 1.5A  
±3% AT 1.51 TO 2.5A  
Light source: Halogen lamp 12v / 20w  
Zero: Automatic  
Settings: Monochromatic and  
Biochromatic readings  
Detector: Schottkey type  
photodiode - silicon

## Thermostat system

Accuracy: ± 0.1°C  
Peltier regulated 25°, 30° and 37°C / RT

## Cuvettes

Flow cell of 18 µL  
Removable Cuvettes: Flowcell, Square semi-  
micro plastic, round test tubes ø 13mm

## Interface

Screen: Graphic LCD 240x128 pixels  
Keyboard: Tactile Soft - Touch / USB\*  
Printer: Built-in 57mm thermal printer  
RS - 232 for pc connection  
Parallel port for 80 column dot matrix printer\*

## Aspiration System

Bi-Directional peristaltic pump /  
Sipping volume programmable from  
100 µL to 2000 µL  
Air purge volume : programmable  
from 30µL to 150 µL.

## Power / Dimensions

Voltage: 110 - 220V / 50 - 60 Hz  
Power Supply: <80W  
Temperature: 10°C to 40°C  
Relative humidity: ≤80%  
Dimensions: 38cm X 41cm X 15cm

## Programming

Table of tests: up to 235  
Table of units: up to 9 units  
Memory: 1000 Test results  
Quality control storage of the last 30 results

## Quality control

3 controls per test - Low, normal & high  
Levy-Jennings charts

## Ordering Information

Catalog #	Description
830-3000	Model RX-50 Bio-Chemistry semi auto analyzer includes: Specification as per the list, spare fuse, dust cover, operating manual, 2 thermal printer rolls, waste bottle with stand
830-3001	Model RX-50 Bio-Chemistry semi auto analyzer includes: Flow cell: 32 µL Filters: 340, 405, 450, 505, 546, 578, 630 & 670nm QC: 3 levels USB Keyboard, power adapter, dust cover, operating manual, 2 thermal printer roll, waste bottle with stand
830-3002	Model RX-50 Bio-Chemistry semi auto analyzer includes: Flow cell: 32 µL Filters: 340, 405, 450, 505, 546, 578, 630 & 670nm Stepper motor driven peristaltic pump, power cord, spare fuse, dust cover, operating manual, 2 thermal printer roll, waste bottle with stand
830-3003	Model RX-50 Bio-Chemistry semi auto analyzer includes: Filters: 340, 405, 505, 546, 578 & 630 nm +2 extra position Memory: 2000 test results Power cord, spare fuse, dust cover, operating manual, 2 thermal printer roll, waste bottle with stand
830-3004	Model RX-50 Bio-Chemistry semi auto analyzer includes: Halogen Lamp: 6V-10 W Filters: 340, 405, 450, 505, 546, 578, 630 & 670nm Memory: 2000 test results Peristaltic pump, power cord, spare fuse, dust cover, operating manual, 2 thermal printer roll, waste bottle with stand